

Talo 90-120-150 180-240 suspension

design

Neil Poulton
2001

Artemide®

Awards

Prix "L'Observateur du Design 2002"
"Etoile 2002" - Paris (France)

Design Innovationen - Design
Zentrum Nordrhein Westfalen
Reddot Design Award
2002 - Essen (Deutschland)

iF Product Design Award
2002 - Hannover (Deutschland)

Compasso d'oro / A.D.I. - Segnalazione
2002 - Milano (Italia)

Intel Design 2003
Categoria design "Augusto Morello"
III edizione - Milano (Italia)

Light emission




Colors



white



silver/grey



Talo 90 suspension

fluorescent source

- 1 x 39W (G5/T5 HO)

Talo 120 suspension


fluorescent source

- 1 x 54W (G5/T5 HO)

Talo 150 suspension

fluorescent source

- 1 x 80W (G5/T5 HO)



Talo 180 suspension

fluorescent source

- 2 x 39W (G5/T5 HO)

Talo 240 suspension

fluorescent source

- 2 x 54W (G5/T5 HO)



Cable suspension mounted luminaires for direct and indirect fluorescent lighting.

Materials:

- thermoplastic resin ceiling rose; painted aluminum body; opal polycarbonate lower diffuser
- available mono or double tube (on same line), in different lengths according to the power of the light source
- the suspension cables are also feed cables

Suspensions avec éclairage fluorescent direct et indirect.

Matériaux:

rosace en résine thermoplastique; corps en aluminium peint; diffuseur inférieur en polycarbonate opale • tube unique ou double (sur la même ligne), différentes longueurs offertes selon la puissance de la source lumineuse • les câbles de suspension servent également de cordons d'alimentation

Luminarias suspendidas por cable para iluminación fluorescente directa e indirecta.

Materiales:

roseta de techo de resina termoplástica; cuerpo de aluminio pintado; difusor inferior de polycarbonato opalino • disponible con tubo simple o doble (en la misma línea), en varias longitudes según la potencia de la fuente de iluminación • los cables de suspensión también funcionan como cables de alimentación

